

Fixed radius										
Diameter	R 1	R 2	R 3	R 4	Wall thickness	Fe 235, 355	Aisi 304 EN 1.4301/7	Aisi 316 EN 1.4401	Aisi 441 EN 1.4509	Aluminum
26,9	65				2,6-3,6	X				
28,0	70				1,5-2,0	X	X	X	X	
33,7	80				2,6-3,6	X				
38,0	75				1,5-3,0	X	X	X	X	
40,0	80				1,5	X	X	X		
42,4	85				1,5-3,6	X	X	X		
45,5	90				10-20	X				
48,3	96				1,5-3,6	X	X	X		
50,8	70	85	140		1,5-3,2	X	X	X		
55,0	70				1,5-3,2	X				
57,0	85				1,5-3,2	X	X	X		
60,3	85	120			1,5-3,2	X	X	X		
63,5	85				1,5-3,6	X	X	X	X	
68,0	100				1,5-3,6	X	X	X		
70,0	160				1,5-3,6	X	X	X		
76,1	76	100	150	160	1,5-10,0	X	X	X	X	
88,9	120	170			2,0-10,0	X	X	X	X	
90,0	150				2,5					X
101,6	101,6	141	170		2,0	X	X	X	X	
108,0	170				2,0	X	X	X		
114,3	190				2,0	X	X	X	X	
120,0	200				2,0	X	X	X		
127,0	180	200			2,0	X	X	X	X	

Variable radius, rolling		
Diameter	Minimi radius	Wall thicness
76,1	600	2,0 / 5,0 / 6,3
88,9	750	2,0